

STANDARD GRADED 20'

INSIDE LENGTH	6' 11.89"	1.89 m
INSIDE WIDTH	7' 8.31"	2.31 m
INSIDE HEIGHT	7' 3.38"	2.38 m
DOOR WIDTH	8' 2.28"	2.28 m
DOOR HEIGHT	6' 2.28"	2.28 m
CAPACITY	133.118	50.56 m ³
TARE WEIGHT	4160	229 kg
MAX. CAPACITY	42950	120 kg

STANDARD CUBE 40'

INSIDE LENGTH	39' 5.01"	12.01 m
INSIDE WIDTH	7' 8.31"	2.33 m
INSIDE HEIGHT	7' 8.12"	2.69 m
DOOR WIDTH	8' 2.33"	2.33 m
DOOR HEIGHT	6' 2.56"	2.56 m
CAPACITY	239.137	8.23 m ³
TARE WEIGHT	6000	1500 kg
MAX. CAPACITY	59200	12 kg

OPEN TOP 20'

INSIDE LENGTH	19' 4.69"	5.89 m
INSIDE WIDTH	7' 1.81"	2.11 m
INSIDE HEIGHT	7' 1.33"	2.13 m
DOOR WIDTH	7' 0.28"	2.28 m
DOOR HEIGHT	7' 1.18"	2.18 m
CAPACITY	136.213	3.6 m ³
TARE WEIGHT	5160	194 kg
MAX. CAPACITY	620	100 kg

OPEN TOP 40'

INSIDE LENGTH	39' 5.01"	12.01 m
INSIDE WIDTH	7' 8.31"	2.33 m
INSIDE HEIGHT	7' 1.33"	2.13 m
DOOR WIDTH	7' 8.33"	2.33 m
DOOR HEIGHT	7' 1.26"	2.26 m
CAPACITY	213.66	5.4 m ³

TARE	8190 kg	150 kg
MAX. CAP.	25720 kg	1630 kg

REEFER 20'		
INSIDE LENGTH	5.83 m	
INSIDE WIDTH	2.26 m	
INSIDE HEIGHT	2.26 m	
DOOR WIDTH	2.26 m	
DOOR HEIGHT	2.20 m	
CAPACITY	28.13 m ³	
TARE	7190 kg	193 kg
MAX. CAP.	25720 kg	156 kg

REEFER 40' HIGH CUBE		
INSIDE LENGTH	11.55 m	
INSIDE WIDTH	2.28 m	
INSIDE HEIGHT	2.48 m	
DOOR WIDTH	2.28 m	
DOOR HEIGHT	2.43 m	
CAPACITY	63.65 m ³	
TARE	7190 kg	490 kg
MAX. CAP.	25720 kg	109 kg

FLAT RACK 20'		FLAT RACK 40'	
INSIDE LENGTH	2.06 m		
INSIDE WIDTH	2.08 m		
INSIDE HEIGHT	1.95 m		
TARE	1479 kg		
MAX. CAP.	25720 kg		